

TECHNICAL DATA SHEET

AC PRIMER SEALER

Excellent Adhesion Anti Corrosion Metal Roof Primer

DESCRIPTION

PROMATE AC PRIMER SEALER is an anti corrosion metal roof primer specially designed by latest Australia Technologies. It is formulated based on an acrylic resin with exceptional adhesion properties. The excellent adhesion, very low moisture permeability and anti-corrosion properties makes **PROMATE AC PRIMER SEALER** the ideal primer sealer for most rusty steel, galvanized iron, metal and various surfaces.

FEATURES AND BENEFITS

<ul style="list-style-type: none"> ✚ Exceptional Bond ✚ Very low water permeability ✚ Tough film ✚ Rapid drying ✚ Easy application with simple procedures 	<ul style="list-style-type: none"> ✚ Non flammable, non toxic, non corrosive ✚ Contains effective corrosion inhibitor to provide long-term protection ✚ May be top coated by most top coat
--	---

AREA OF USE

<ul style="list-style-type: none"> ✚ Iron ✚ Galvanized Iron ✚ Zincalume 	<ul style="list-style-type: none"> ✚ Steel ✚ Aluminum
--	---

APPLICATION GUIDE

- ✚ Surfaces must be clean, dry and free of dust and in a sound condition.
- ✚ Corroded areas must be wire brushed to remove all loose materials prior to applying **PROMATE AC PRIMER SEALER**.
- ✚ Can be applied by airless spray, brush or roller
- ✚ Can be recoat if necessary in 1 hour time. Subject to weather condition.
- ✚ Wash application tools and equipment with clean water before product dries.

COVERAGE

10 – 12M²/L per coat (approx). Subject to surface condition.

PHYSICAL PROPERTIES

Appearance	:	White liquid
Boiling Point	:	Approximately 100°C (water)
Vapour Pressure	:	17 (water) mm Hg @ 22°C (water)
Specific Gravity	:	1.400

HEALTH & SAFETY

Safety Precautions

- ✚ Provide good ventilation – open windows and doors and use circulating fans
- ✚ If product is splashed on skin it should be washed off with water before it can dry
- ✚ Wear gloves and eye protection during application
- ✚ Normal protective clothing should be worn.

First Aid

Skin Contact: Wash immediately and thoroughly with soap and water.

Swallowed: Rinse mouth and throat with water. Do not induce vomiting and drink alcohol. Drink large amount of water. Seek medical if irritation occurs.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

PACKING, TRANSPORT AND STORAGE

Sizes: 5L / 18L	Dangerous Goods Class:	N/A
Store in a cool dry place	Flash Point:	N/A
	Shelf Life:	15 months

DISCLAIMER

Any Advice, recommendation, information, assistance or service provided by Pro Builders in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is prove defective, our liability is limited to the replacement of the product.