

TECHNICAL DATA SHEET ACRYLIC PRIMER SEALER

Acrylic Polymer Roof Primer Sealer

DESCRIPTION

PROMATE ACRYLIC PRIMER SEALER is a roof primer specially designed by latest Australia Technologies. It is waterborne 100% acrylic resin formula that provides a high degree of adhesion and excellent penetration to asbestos, clay or concrete roof tiles and fibrous cement. It develops water resistance very quickly to become a very efficient surface sealer that reduces the absorption loss of subsequent finishes.

FEATURES AND BENEFITS

- Excellent sealing properties
- Reduces coverage loss of subsequent coatings
- Excellent adhesion
- Water resistance
- Water based

- Non flammable, non toxic, non corrosive
- Fast drying time
- Durable acrylic polymer
- Easy application with simple procedures

AREA OF USE

Sealer for asbestos sheets, clay or concrete roof tiles prior to coating with Promate Acrylic Gloss

APPLICATION GUIDE

- Surfaces must be free of all contamination
- Remove all biological growth deposits and chalking or flaking paint, etc.
- Use high-pressure water jet to completely clean area to be coated.
- Can be applied by airless spray, brush or roller
- Only single coat is require in most application.
- ♣ Can be recoat if necessary in 30 minutes to 1 hour time. Subject to weather condition.
- Wash application tools and equipment with clean water before product dries.

COVERAGE

10 – 12M²/L per coat (approx). Subject to surface condition.

Email: sales@probuildersmarketing.com

PHYSICAL PROPERTIES

Appearance : Milky white liquid. Mild odour

Boiling Point : Approximately 100°C (water)

Vapour Pressure : 17 (water) mm Hg @ 22°C (water)

Specific Gravity : 1.0

HEALTH & SAFETY

Safety Precautions

- ♣ Provide good ventilation open windows and doors and use circulating fans
- If product is splashed on skin it should be washed off with water before it can dry
- Wear gloves and eye protection during application
- Normal protective clothing should be worn.

First Aid

Skin Contact: Wash immediately and thoroughly with soap and water.

Swallowed: Rinse mouth and throat with water. Do not induce vomiting and drink alcohol. Drink large amount of water. Seek medical if irritation occurs.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

| PACKING, TRANSPORT AND STORAGE | |
|--------------------------------|------------------------|
| Sizes: 5L / 18L | Dangerous Goods Class: |

Store in a cool dry place Flash Pont: N/A

Shelf Life: 15 months

DISCLAIMER

Any Advice, recommendation, information, assistance or service provided by Pro Builders in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is prove defective, our liability is limited to the replacement of the product.



N/A