

TECHNICAL DATA SHEET

ACRYLIC ROOF COATING

Acrylic Polymer Pigmented Roof Coating

DESCRIPTION

PROMATE ACRYLIC ROOF COATING is 100% water based acrylic polymer formulation, specially designed by latest Australia Technologies to seal, restore and rejuvenate old and aged roofs to their former colours, or to a new and more modern colour. **PROMATE ACRYLIC ROOF COATING** is a highly durable flexible finish, formulated for excellent resistance to all types of weather. It is not only rejuvenates and restores but it also improved the weather ability of the roof, and also inhibits the growth of mould and lichen.

FEATURES AND BENEFITS

<ul style="list-style-type: none"> Waterproof Superior "Full Acrylic" durability Rapid hardness development Low dirt pick-up Increase lifespan Excellent Flexibility New colour and aesthetic appear 	<ul style="list-style-type: none"> Resistance to water whitening Colour retentive Chalk fade resistance High gloss retention Non flammable, non toxic, non corrosive Fast drying time Available in a range of popular colours
---	--

AREA OF USE

<ul style="list-style-type: none"> Concrete roof tiles Clay tiles (Unglazed) Metal deck Galvanized iron Asbestos 	<ul style="list-style-type: none"> Fascias Guttering Timber Weatherboards Previously painted surfaces.
---	---

APPLICATION GUIDE

- All surfaces to be free of surface contaminations. Use high-pressure water jet to completely clean area to be coated.
- Can be applied by airless spray, brush or roller
- Metal surface to be spot primed.
- All previous paint should be free of chalking. All loose and peeling paint must be removed.
- Several deteriorated or porous cement tile surfaces will require a coat of **PROMATE ACRYLIC PRIMER SEALER** to re-seal the surface and follow by two coats of **PROMATE ACRYLIC ROOF COATING**.
- Can be recoat if necessary in 30 minutes to 1 hour time. Subject to weather condition.
- Remove any dried paint and wash application tools and equipment with clean water.

COVERAGE





8 – 10M²/L per coat (approx). Subject to surface condition.

PHYSICAL PROPERTIES

Appearance	:	Pigmented opaque liquid
Boiling Point	:	Approximately 100°C (water)
Vapour Pressure	:	750 (water) mm Hg @ 26°C (water)
Specific Gravity	:	1.3510

HEALTH & SAFETY

Safety Precautions

-  Provide good ventilation – open windows and doors and use circulating fans
-  If product is splashed on skin it should be washed off with water before it can dry
-  Wear gloves and eye protection during application
-  Normal protective clothing should be worn.

First Aid

Skin Contact: Wash immediately and thoroughly with soap and water.

Swallowed: Rinse mouth and throat with water. Do not induce vomiting and drink alcohol. Drink large amount of water. Seek medical if irritation occurs.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

PACKING, TRANSPORT AND STORAGE

Sizes: 5L / 18L	Dangerous Goods Class:	N/A
Store in a cool dry place	Flash Point:	N/A
	Shelf Life:	15 months

DISCLAIMER

Any Advice, recommendation, information, assistance or service provided by Pro Builders in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is prove defective, our liability is limited to the replacement of the product.